



The package included:

- * 8CH H.265+ 3MP NVR (not included HDD) X 1
- * Wireless H.265+ 3MP IP Cameras X 4
- * DC 12V 1A Power adapter X4
- * DC 12V 2A Power adapter X1
- * USB Mouse X 1
- * User Manual X1
- * Screw bag X4

WiFi NVR Specification

System	Model	ITY-K6004B5(3Mp)
	Main processor	XM8516D
	screen	10.1 inch 1280*800
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4
	Video input (IP)	4*3MP
	Access bandwidth	24Mbps
	Forwarding bandwidth	24Mbps
	Video compression	H.265+
	Display quality	Max 3MP
	Playback quality	3MP
	Decode	4*3MP
	VR	Unsupport
	Motion detection	Support(depend on camera)

Audio	Audio compression	G.711A
	Intercom	Unsupport
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	4*3MP
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD、 Network,SD card
	Backup mode	Network backup, USB hard disk, USB burner,
External Interface	Video output	1ch HDMI HD output
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI
	USB interface	2*USB2.0 ports
	HDD	1* SATA+1 SD card
	ESATA	No
	Serial interface	No
Other	ONVIF	No
	Power supply	12V 2A
	Power Consumption	<10W(Without HDD)
WiFi Camera Specification		
To configure	Processor + sensor	XM530 Ai+2.0M 1/3"Q03 CMOS sensor
	Low illumination	Color: 0.1 Lux; B/W: 0.01 Lux
	Effective pixel	HD 3MP
	Lens	HD lens 3.6MM
	Infrared lamp	8pcs X \varnothing 5 Lamp beads
	Infrared distance	150~200m
	Day&night	IR cut filter with auto switch

General	setting	Saturation, brightness and contrast ; are adjustable through IE browser or client software.
	Video compression	H.265+
	temperature	-10°C-+ 60°C
	humidity	10%-90% RH
	Power supply	DC12V 1A
	Consumption	MAX 6W
	Waterproof grade	IP66
	Dimension	221*120*92;
	Weight	0.5 kg

www.innotronik.com